## MANUAL TOTAL STATION





Stable performance with accurate long-range distance measurement, clear, easy-to-read display and practical onboard software. ARMOR 3 offers a durable and versatile solution to your survey and construction tasks.





#### **Efficient Operation**

Customizable Hot Keys Shortcuts Trigger Button



#### **Trusted Measurement**

2" Angle Accuracy 1,500m NP Range Stable. Reliable



#### **Data Transfer**

USB drive Bluetooth



### **Long Duration**

Smart Battery Manager 3,000mAh Battery 16h working time

# **SPECIFICATIONS**

TELESCOPIC

Length 154mm

Telescopic: 45mm; EMD: 50mm Diameter

Magnification 30x **Image** Erect Field of View 19301

Resolving Power 3" Minimum Focus 1.5m

DISTANCE

Single Prism Range 5,000m

±(2mm+2mm\*D)m.s.e Accuracy

Non-prism Range 1.500m

Accuracy ±(3mm+2mm\*D)m.s.e Measuring Time Fine: 0.3s; Normal: 0.2s

Meteorologic Correction Auto Sensor Prism Constant Manual

ANGLE

Accuracy

Method Absolute Encoding **Detecting System** H: dual; V: dual

1"/5"/10" Minimum Reading

Diameter of Circle 79mm

Vertical Angle 0° Zenith: 0°; Horzontal: 0° 360°/400gon/6400mil Unit

DISPLAY

Display Unit 2.6" with backlight, 6 lines

No. of Displays

Keyboard Alphanumeric PLUMMET - LASER

Class II red laser Type

<0.4mm @ 1.5m height Accuracy Spot Diameter <1.5mm @ 1.5m height

> - OPTICAL \*optional

Erect Image Magnification 3X

Foucing Range 0.3m - ∞

Field of View 50

**TILT CORRECTION** 

Tilt Sensor Dual axis Method Liquid electric

Range 4' Resolution 1"

LEVEL

Plate Level 30"/2mm

Circular Level 8'/2mm

DATA INTERFACE

Internal Memory > 10,000 points

Data Interface USB2.0

Wireless \* Bluetooth 2.1, WT12

**GENERAL** 

Quick-meas Button Yes

Weight 5.4kg

Dimension 353 (H) \* 206 (L) \* 200 (W) mm

Operating Temperature -20°C to 50°C

Battery Li-on battery, 7.4V, 3000mAh

Water & Dust Proof **IP55** Working Duration 16h





C-201 Yunsheng Science Park, No.11 Middle Guangpu Road, Huangpu District, Guangzhou 510663, China sales@stecprecision.com support@stecprecision.com





